

Waveform Lighting's T5 LED linear light fixtures offer 95 CRI color accuracy in a convenient, integrated fixture form factor. The integrated LED fixture is extremely simple to set up, and does not require any external housing, ballasts, fixtures or power supplies. Simply plug the fixture into any standard power outlet.

Despite its simplicity, the T5 LED linear light fixture can be installed virtually anywhere, ranging from portable or temporary installation using the include magnet clips, installation along interior crossbeams, or as a fluorescent lamp replacement in an existing lamp fixture. Multiple fixtures can be daisy-chained up to 70 feet (21 meters) using the supplied cables or in a gapless, flush connection.

These fixtures are offered in 2-ft and 4-ft configurations, and are bright enough to directly replace T8 fluorescent lamps of equal length.

**FEATURES**

- Integrated LED light fixture with simple power cord and plug-in installation
- No separate fixture, housing, power supplies, drivers or ballasts needed
- Mount onto virtually any surface using included screws or magnets
- Ultra-high 95 CRI, R9 > 90; available in 4000K, 5000K or 6500K
- For indoor use only



**PHOTOMETRIC SPECIFICATIONS**

<b>Light output (2 ft):</b>	900 lumens	<b>CRI Ra:</b>	95+
<b>Light output (4 ft):</b>	1800 lumens	<b>CRI R9:</b>	90+
<b>Luminous efficacy:</b>	100 lm/W	<b>TM-30-15 R<sub>r</sub>/ R<sub>g</sub>:</b>	90+/100
<b>Light distribution:</b>	320 degrees		

Download full photometric reports at <https://www.waveformlighting.com/photometrics>

**ELECTRICAL SPECIFICATIONS**

<b>Fixture connection:</b>	Two-prong US-style plug / C8 plug
<b>Power:</b>	9 watts (2-ft) / 18 watts (4-ft)
<b>Input voltage:</b>	120 – 277V AC
<b>Input frequency:</b>	50 – 60 Hz
<b>Power factor:</b>	0.9
<b>Dimmer compatible?</b>	No


**MECHANICAL SPECIFICATIONS**

<b>Length:</b>	19.7 in (500 mm) / 43.3 in (1100 mm)
<b>Diameter / Width:</b>	0.79 in (20 mm)
<b>Lamp material:</b>	Polycarbonate

**PART NUMBERS AND ORDERING**

<b>4000K / 2-ft</b>	4026.2F.40
<b>5000K / 2-ft</b>	4026.2F.50
<b>6500K / 2-ft</b>	4026.2F.65
<b>4000K / 4-ft</b>	4026.4F.40
<b>5000K / 4-ft</b>	4026.4F.50
<b>6500K / 4-ft</b>	4026.4F.65

**MECHANICAL DRAWING & DIMENSIONS**



Daisy-Chaining Using Cable



Daisy-Chaining Using Integrated Plugs



Fixture Ends with Integrated Plugs



Fixture End with Plug-in Cord

**INCLUDED ACCESSORIES**



Power Cord (1 pcs)  
Length: 12 inches (30 cm)



Daisy Chain Cord (1 pcs)  
Length: 12 inches (30 cm)



Screws, Anchors & Mounting Clips (2 pcs)



Magnets & Mounting Clips (2 pcs)